

Amendments to the Claims

The listing of claims will replace all prior versions, and listings of claims in the application.

1. (Currently Amended) A method for classifying a data packet in a network interface, comprising the steps of:
 - (a) receiving a plurality of classification parameters;
 - (b) generating a plurality of program modules, each of said plurality of program modules for testing for adherence to at least one corresponding classification parameter, wherein the program modules contain an operation code field and one or more operand fields;
 - (c) receiving the data packet;
 - (d) generating a header, said header indicating whether one or more predefined fields are present in the data packet and identifying a location of said one or more predefined fields in the data packet when present, wherein the location is identified by an address value that defines the position of the one or more predefined fields within the data packet in terms of an exact position or in terms of a position plus an offset;
 - (e) executing each of said plurality of program modules based on said operation code field, wherein each of said plurality of program modules receives said header and generates a test result based on contents of said header and contents of the data packet; and
 - (f) processing the data packet based on said test results from said plurality of program modules.

2. (Original) The method of claim 1, wherein said classification parameters comprise DOCSIS classification parameters.

3. (Original) The method of claim 1, wherein step (f) comprises applying packet header suppression to the data packet based on said test results from said plurality of program modules.

4. (Original) The method of claim 1, wherein step (f) comprises transmitting the data packet over a selected service flow based on said test results from said plurality of program modules.

5. (Original) The method of claim 1, wherein step (f) comprises rejecting the data packet for violating classification parameters based on said test results from said plurality of program modules.

6. (Original) The method of claim 1, wherein step (a) comprises receiving a configuration file, said configuration file including said plurality of classification parameters.

7. (Original) The method of claim 1, wherein step (a) comprises receiving a cable modem configuration request, said cable modem configuration request including said plurality of classification parameters.

8. (Original) The method of claim 1, wherein step (a) comprises receiving a dynamic service message, wherein said dynamic service message includes said plurality of classification parameters.

9. (Original) The method of claim 1, wherein said steps (a) and (b) occur as part of a cable modem registration process.

10. (Original) The method of claim 1, wherein said steps (a) and (b) occur during generation of a new service flow.

11. (Original) The method of claim 1, wherein said header is concatenated to the data packet.

12. (Original) The method of claim 1, wherein step (e) comprises executing each of said plurality of program modules in parallel.

13. (Original) The method of claim 1, wherein step (f) comprises the steps of:

combining said test results from said plurality of program modules using a logical AND operation; and

processing the data packet based on a result of said logical AND operation.

14. (Currently Amended) A method for classifying a data packet in a network interface, comprising the steps of:

- (a) receiving a plurality of classification parameters;
- (b) generating a plurality of optimized program modules, each of said plurality of program modules for testing for adherence to at least one corresponding classification parameter, wherein the plurality of optimized program modules contain an operation code field and one or more operand fields;
- (c) receiving the data packet;
- (d) generating a header, said header indicating whether one or more predefined fields are present in the data packet and identifying a location of said one or more predefined fields in the data packet when present, wherein the location is identified by an address value that defines the position of the one or more predefined fields within the data packet in terms of an exact position or in terms of a position plus an offset;
- (e) serially executing said plurality of program modules based on said operation code field, wherein each of said plurality of program modules receives said header and generates a test result based on contents of said header and contents of the data packet used to generate the header, until one of said plurality of program modules generates a failing test result; and
- (f) processing the data packet based on whether a failing test result was generated in step (e).

15-26. (Cancelled)

27. (Currently Amended) A computer program product comprising a computer usable medium having computer program logic for enabling a processor in a network interface to classify a data packet, comprising:

first computer control logic means for enabling the processor to receive a plurality of classification parameters;

second computer control logic means for enabling the processor to generate a plurality of program modules, each of said plurality of program modules for testing for adherence to at least one corresponding classification parameter, wherein the program modules contain an operation code field and one or more operand fields;

third computer control logic means for enabling the processor to receive the data packet;

fourth computer control logic means for enabling the processor to generate a header, said header indicating whether one or more predefined fields are present in the data packet and identifying a location of said one or more predefined fields of the data packet when present, wherein the location is identified by an address value that defines the position of the one or more predefined fields within the data packet in terms of an exact position or in terms of a position plus an offset;

fifth computer control logic means for enabling the processor to execute each of said plurality of program modules based on said operation code field, wherein each of said plurality of program modules receives said header and generates a test result based on contents of said header and contents of said data packet; and

sixth computer control logic means for enabling the processor to process the data packet based on said test results from said plurality of program modules.

28. (Previously Presented) The computer program product of claim 27, wherein said first computer control logic means comprises means for enabling the processor to receive DOCSIS classification parameters.

29. (Previously Presented) The computer program product of claim 28, wherein said sixth computer control logic means comprises means for enabling the processor to apply packet header suppression to the data packet based on said test results from said plurality of program modules.

30. (Previously Presented) The computer program product of claim 28, wherein said sixth computer control logic means comprises means for enabling the processor to transmit the data packet over a selected service flow based on said test results from said plurality of program modules.

31. (Previously Presented) The computer program product of claim 28, wherein said sixth computer control logic means comprises means for enabling the processor to reject the data packet for violating classification parameters based on said test results from said plurality of program modules.

32. (Previously Presented) The computer program product of claim 28, wherein said first computer control logic means comprises means for enabling the

processor to receive a plurality of classification parameters retrieved from a configuration file.

33. (Previously Presented) The computer program product of claim 28, wherein said first computer control logic means comprises means for enabling the processor to receive a plurality of classification parameters retrieved from a cable modem configuration request.

34. (Previously Presented) The computer program product of claim 28, wherein said first computer control logic means comprises means for enabling the processor to receive a plurality of classification parameters retrieved from a dynamic service message.

35. (Previously Presented) The computer program product of claim 28, wherein said first computer control logic means and said second computer control logic means are executed as part of a cable modem registration request.

36. (Previously Presented) The computer program product of claim 28, wherein said first computer control logic means and said second computer control logic means are executed during generation of a new service flow.

37. (Previously Presented) The computer program product of claim 28, wherein said fourth computer control logic means comprises means for enabling the processor to concatenate said header to the data packet.

38. (Previously Presented) The computer program product of claim 28, wherein said fifth computer control logic means comprises means for enabling the processor to execute each of said plurality of program modules in parallel.

39. (Previously Presented) The computer program product of claim 28, wherein said sixth computer control logic means comprises means for enabling the processor to combine said test results from said plurality of program modules using a logical AND operation and process the data packet based on a result of said logical AND operation.